

HELI



4.0-5.0 t

G3 Series LPG Forklift Truck

More energy saving



Stronger traction performance



Higher handling efficiency



Improved lateral stability high bearing capacity



Design Characteristics

Identification		CP(Q)YD40-KUG3	CP(Q)YD45-KUG3	CP(Q)YD50-KUG3
Model		CP(Q)YD40-KUG3	CP(Q)YD45-KUG3	CP(Q)YD50-KUG3
Rated capacity	kg	4000	4500	5000
Load center	mm	500	500	500
Dimensions				
Overall height(overhead guard)	mm	2350	2350	2350
Overall length(with fork)	mm	4255	4275	4325
Overall width (single Tyre)	mm	1510	1510	1510
Min.outside turning radius	mm	2850	2880	2930
Weight				
Total weight	kg	6250	6510	6920
Wheels, chassis				
Tyre size(front)		8.25-15-14PR	300-15-18PR (Double-tyre 8.25-15-14PR)	300-15-18PR (Double-tyre 8.25-15-14PR)
Tyre size(rear)		7.00-12-14PR	7.00-12-14PR	7.00-12-14PR
Performance				
Max.traveling speed (Loaded/Unloaded)	km/h	25/26	25/26	25/26
Engine model		Kubota Certified WG3800		