


# XG0607DC

## Scissor lift

### FEATURES

#### PRODUCTIVITY

2 rear driving wheels  
 25% theoretical gradeability  
 Battery charge indicator and diagnostic display  
 Manual platform lowering valve  
 Both platform and ground control panel with emergency stop button  
 Rear wheel multi-disc brakes  
 Manual brake release  
 Solid non-marking tires  
 Mobile pothole protection  
 Tilt alarm  
 Hourmeter record  
 Lift and lower alarm  
 Horn  
 Dual flashing beacons  
 Drive alarm  
 Overload alarm



### OPTIONS

Platform working light  
 Air-line to platform  
 AC power to the platform  
 Lithium battery

Item	Unit	XG0607DC
Lift capacity	kg	240
Lift capacity of auxiliary platform	kg	100
Occupant Capacity	-	2
Working height	m	5.9
Platform height	m	3.9
Length of auxiliary platform	mm	600
Ground clearance(Pot hole protector – raised/lowered)	mm	65/15
Turning radius(inside/outside)	m	0.4/1.55
Drive motor	kW	0.45
Lift motor	kW	1.3
Drive speed-full retracted	km/h	4.0
Drive speed-full extended	km/h	0.5
Lift/Lower time	s	27~37/23~33
Gradeability	%	25
Tilt alarm(side/forward and backward)	°	1.5/3
Batteries	V/Ah	2 x 12/75
Charger	V/A	24/15
Tires	-	254 x 76
Weight	kg	900
a Length(without ladder)	mm	1450(1290)
b Width	mm	760
c Height(platform folded)	mm	2020(1660)
d x e Platform size(Length x Width)	mm	1290 x 700
f Wheelbase	mm	1030