


XG0807AC/XG0807ACW

Scissor lifts

FEATURES

PRODUCTIVITY

2 front driving wheels
 25% theoretical gradeability
 Battery charge indicator and diagnostic display
 Manual platform lowering valve
 Both platform and ground control panel with emergency stop button
 Front wheel multi-disc brakes
 Manual brake release
 Solid non-marking tires
 Mobile pothole protection
 Tilt alarm
 Hourmeter record
 Lift and lower alarm
 Horn
 Dual flashing beacons
 Drive alarm
 Overload alarm



OPTIONS

Platform working light
 Air-line to platform
 AC power to the platform
 Lithium battery

Item	Unit	XG0807AC	XG0807ACW
Lift capacity	kg	230	230
Lift capacity of auxiliary platform	kg	115	115
Occupant Capacity	-	2	2
Working height	m	7.8	7.8
Platform height	m	5.8	5.8
Length of auxiliary platform	mm	900	900
Ground clearance(Pot hole protector – raised/lowered)	mm	71/20	71/20
Turning radius(inside/outside)	m	0/1.75	0/1.75
Drive motor	kW	0.5	0.5
Lift motor	kW	3.3	3.3
Drive speed-full retracted	km/h	4.5	4.5
Drive speed-full extended	km/h	0.8	0.8
Lift/Lower time	s	13~30/25~35	13~30/25~35
Gradeability	%	25	25
Tilt alarm(side/forward and backward)	°	1.5/3	1.5/3
Batteries	V/Ah	4 x 6/280	4 x 6/280
Charger	V/A	24/30	24/30
Tires	-	323 x 100	323 x 100
Weight	kg	1550	1580
a Length(without ladder)	mm	1900(1680)	1900(1680)
b Width	mm	760	810
c Height(platform folded)	mm	2160(1830)	2160(1830)
d x e Platform size(Length x Width)	mm	1670 x 740	1670 x 740
f Wheelbase	mm	1360	1360